

**Amendments to the Claims:**

This Listing of Claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1-4. (Cancelled).

5. (Previously presented) A method for revision of an implanted cannulated bone screw, comprising the steps of:

- inserting a cannulated screwdriver into a screw head of said cannulated bone screw;
- introducing a removal device into said cannulated screwdriver;
- screwing a threaded distal end of said removal device into a corresponding threaded portion of said cannulated screw; and

- simultaneously unscrewing said screw using said cannulated screwdriver and pulling said screw using a handle located on a proximal end of said removal device; wherein:

- said bone screw secures a clamping element to a bone segment;
  - a locking mechanism secures said bone screw to said clamping element, said locking mechanism comprising:

- at least two snap catches protruding from a bone-contacting surface of said clamping element and spaced around an edge of a screw hole; and

- a circumferential groove located on a top portion of said screw below a screw head for receipt of said snap catches; and

- said snap catches interlock with said groove to secure said bone screw to said clamping element when said bone screw is screwed into said bone segment through said screw hole of said clamping element.

6. (Original) A method in accordance with claim 5, wherein the distal end of said removal device is externally threaded and the corresponding threaded portion of said screw is an internally threaded portion.

7. (Cancelled).

8. (Cancelled).

9. (Previously presented) A method in accordance with claim 5, wherein:  
said snap catches comprise spikes adapted to function as bone anchors.

10. (Original) A method in accordance with claim 9, wherein:  
said spikes comprise elastic spring elements; and  
said elastic spring elements snap into said groove when said bone screw is inserted into said clamping element.

11. (Previously presented) A method in accordance with claim 5, wherein a greater axial force is needed to remove said screw from said clamping element than is needed to insert said screw into said clamping element.

12. (Previously presented) A method in accordance with claim 5, wherein:  
removal of said screw from said clamping element results in deformation of at least one of  
(i)said snap catches, or (ii) said groove.

13. (Previously presented) A method in accordance with claim 5, wherein:  
said screw comprises a shaft having a conical portion between said groove and threads of said shaft.

14. (Previously presented) A method in accordance with claim 5, wherein:

said groove has a flat edge portion perpendicular to a shaft of said screw; and  
said snap catches have a square end portion for interlocking with said flat edge portion.

15. (Original) A method in accordance with claim 14, wherein:

removal of said screw from said clamping element results in deformation of at least one of  
(i) said square end portion of said snap catches, or (ii) said flat edge portion of said groove.

16. (Previously presented) A method in accordance with claim 5, wherein:

said screw is rotatable after interlocking with said clamping element in order to achieve  
further pre-stress between said bone segment and said clamping element.

17. (Currently amended) A method for locking a bone screw to a clamping element, comprising  
the steps of:

providing a clamping element for stabilizing bone segments, having at least two snap  
catches protruding from a bone-contacting surface of said clamping element and spaced around an  
edge of a screw hole;

providing a cannulated bone screw having a circumferential groove located on a top  
portion thereof below a screw head, for receipt of said snap catches;

positioning said clamping element on a bone segment to be stabilized; and

positioning said screw on the bone segment via a Kirschner wire; and

screwing said bone screw into said bone segment through said screw hole of said  
positioned clamping element in an axial direction until the snap catches interlock with the groove  
of said bone screw to secure said bone screw to said clamping element.

18. (Previously presented) A method for locking a bone screw to a clamping element, comprising  
the steps of:

providing a clamping element for stabilizing bone segments, having at least two snap  
catches protruding from a bone-contacting surface of said clamping element and spaced around an

edge of a screw hole;

providing a bone screw having a circumferential groove located on a top portion thereof below a screw head, for receipt of said snap catches; and

screwing said bone screw into said bone segment through said screw hole of said clamping element until the snap catches interlock with the groove to secure said bone screw to said clamping element;

wherein said snap catches comprise spikes adapted to function as bone anchors.

19. (Original) A method in accordance with claim 18, wherein:

said spikes comprise elastic spring elements; and

said elastic spring elements snap into said groove when said bone screw is inserted into said clamping element.

20. (Original) A method in accordance with claim 17, wherein said bone screw is removable from said clamping element after said snap catches interlock with said groove.

21. (Original) A method in accordance with claim 20, wherein a greater axial force is needed to remove said screw from said clamping element than is needed to insert said screw into said clamping element.

22. (Original) A method in accordance with claim 20, wherein:

removal of said screw from said clamping element results in deformation of at least one of (i) said snap catches, or (ii) said groove.

23. (Original) A method in accordance with claim 17, wherein:

said screw comprises a shaft having a conical portion between said groove and threads of said shaft.

24. (Original) A method in accordance with claim 17, wherein:

said groove has a flat edge portion perpendicular to a shaft of said screw; and  
said snap catches have a square end portion for interlocking with said flat edge portion.

25. (Original) A method in accordance with claim 24, wherein:

removal of said screw from said clamping element results in deformation of at least one of  
(i)said square end portion of said snap catches, or (ii) said flat edge portion of said groove.

26. (Original) A method in accordance with claim 17, wherein:

a targeting instrument is placed on said clamping element; and  
said screw is screwed through said clamping element and into said bone segment via said  
targeting instrument.

27. (Cancelled)

28. (Original) A method in accordance with claim 17, wherein:

said screw is rotatable after interlocking with said clamping element in order to achieve  
further pre-stress between said bone segment and said clamping element.

29. (Currently amended) A method in accordance with claim 17, wherein:

~~said screw is a~~ cannulated screw ~~having~~ has internal threads in a cannulated portion  
thereof.